

Data Sheet FUJITSU Accessories Port Replicators, Cradles and Keyboards for LIFEBOOK and STYLISTIC

Connect to your peripherals. Adapt to the task on demand

Flexibility, expandability, desktop replacement and investment protection are among the benefits of FUJITSU accessories. The port replicators and cradles are designed specifically for your LIFEBOOK, STYLISTIC and mobile CELSIUS, empowering you to connect to your display, keyboard and mouse with one click in the office. Enjoy the versatility of the keyboard options and Active Pen to adapt your tablet to the task on demand while on the move.

Reliability

- High quality and stability
- Everything you need from one source

Ease of Use

- Connect your notebook or tablet instantly to all your peripherals
- One-hand release mechanism (mechanical port replicator)
- Leave your peripherals plugged into the Port Replicator
- Wide range of interfaces
- Hot docking
- Family port replicator supporting products across notebooks, 2 in 1 tablets and mobile workstation over several generations (depending on model)
- Optional power-on button on selected notebooks for extra convenience in the office

Port Replicator for LIFEBOOK S938

Technical details

DC-in	1 (19V)
Power on switch	1
USB 3.1 Gen1 (USB 3.0) total	4
DisplayPort	1 (up to 2560 x 1600)
VGA	1 (up to 1920 x 1200)
DVI	1 (up to 1920 x 1200)
Kensington Lock support	1 (Port Rep only)
LAN / Ethernet (RJ45)	1
Dimensions (W x D x H)	343 x 150 x 30 mm
Weight	0.650 kg
Order code	S26391-F1557-L100
Order code Port Replicator Bundle	S26391-F1557-L110: Port Replicator + 80W AC Adapter (0-Watt Technology) + EU Cable





Port Replicator + 3pin AC 90W w/o Cable for LIFEBOOK T9 Series

Tec	hn	ical	l٨	letai	ilc
iec	ш	ıca	u	eta	112

DC-in	1 (19V)	
Power on switch	1	
USB 3.1 Gen1 (USB 3.0) total	3	
USB Type-C (to Devices)	1	
DisplayPort	1 (up to 2560 x 1600) (not usable in parallel with DVI) In case both are connected DisplayPort has higher priority)	1 (up to 2560 x 1600)
VGA	1	
DVI	1 (up tp 1920 x 1200) (not usable in parallel with DisplayPort)	
Kensington Lock support	2	
LAN / Ethernet (RJ45)	1	
Dimensions (W x D x H)	346 x 130 x 30	
Weight	0.517 kg	
Order code	S26391-F1657-L110	
Order code Port Replicator Bundle	S26391-F1657-E110 Portreplicator + 3pin AC 90W w/o Cable	



Port Replicator for LIFEBOOK U7 and E5 family

DC-in	1 (19 V)
Power on switch	1
Audio: line-in / microphone	1
Audio: line-out / headphone	1
USB 3.1 Gen1 (USB 3.0) total	4 x Type-A 2x Type-C
USB Type-A	4
USB Type-C (to Devices)	2
DisplayPort	2
VGA	1
DVI	1
Kensington Lock support	1 (Portrep only)
Order code	S26391-F1607-L109
Order code Port Replicator Bundle	S26391-F1607-L119



Port Replicator for LIFEBOOK U7 and E5 family with key lock

Technical details

DC-in	1 (19V)
Power on switch	1
Audio: line-in / microphone	1
Audio: line-out / headphone	1
USB 3.1 Gen1 (USB 3.0) total	4x Type-A 2x Type-C
USB Type-A	4
USB Type-C (to Devices)	2
DisplayPort	2
VGA	1
DVI	1
Kensington Lock support	1 (key lock to secure Portrep & System)
Order code	S26391-F1607-L209 S26391-F1607-L209



CELSIUS® H780 Port Replicator Kit

Technical details

1 x
1
X
1 x
1 x
Type-C (Gen1) 2 x; Type-A (Gen1) 4 x;
1x DP1.2 (next to Analog RGB connector; 1x DP1.4 (next to USB3.1 connector); DP++support; x1 through DP on dGPU, x1 via DP-Splitter; DP#1 on Portrep and HDMI on main unit are alternative.
1x (up to 1920x1200 via Portrep internal DP-Splitter)
1x (up to 1920x1200 via Portrep internal DP-Splitter)
1 x
404 x 94 x 28 mm
540 g
S26391-F2249-L300 (Port Replicator and 330W power supply w/o cable)



STYLISTIC Q738/Q739/Q509 Cradle

DC-in	1
USB 3.1 Gen2 total	3
DisplayPort	1
VGA	1
Kensington Lock support	1
Order code	S26391-F3147-L100



Back-lit Keyboard Dock for STYLISTIC Q738/Q739

DC-in	1
LAN / Ethernet (RJ45)	1
Weight	572 g
Order code	S26391-F3149-L22* (* country specific version)



STYLISTIC Q509 Keyboard Dock

Technical details

DC-in	1
Weight	385 g
Order code	S26391-F3159-L2**



Back-lit Keyboard Dock for STYLISTIC Q7310

Technical details

DC-in	1
LAN / Ethernet (RJ45)	1
Order code	S26391-F3399-L221



USB Type-C Port Replicator

Button	1 x button resume from S3 (S4/S5/G3 depending on FUJITSU client, consult manual)
Audio	1 x combo jack for headsets
Network settings	PXE boot MAC address setting (WIN OS)
USB 3.1 Gen2 total	5
USB Type-A	3 x USB 3.1 Gen1, up to 5V/0,9A power output
USB Type-C (to Devices)	1 x USB 3.1 Gen1, up to 5V/3A power output
USB Type-C (to PC/Tablet)	1 x USB 3.1 Gen1, up to 60 W power output (5V, 9V, 12V, 15V, 20V) / 3A Power input 5V/0.9A
DisplayPort	1 x ver. 1.2 resolution up to 4096 x 2160 @24Hz / 3840 x 2160@30Hz depending on system and only one connected display
VGA	1 x resolution up to 1920 x 1200 @60Hz depending on system and connected display
HDMI	1
HDMI text	resolution up to 4096 x 2160 @24Hz / 3840 x 2160@30Hz depending on system and only one connected display
Dimensions (W x D x H)	219 x 75 x 26 mm
Order code	S26391-F3327-L100



Thunderbolt™ 3 Port Replicator

Technical details

(PC)	recillical actalis	
Audio Combo jack for headset usage USB 3.1 Gen2 total 1 x USB3.1 Gen.2 Type A - 5V, 2,4A, 4,5W charging port 2 x USB3.1 Gen.2 Type A - 5V, 09A, 4,5W charging ports 2 x USB3.1 Gen.2 Type C - 5V, 1,5A, 15W charging port 1 x USB3.1 Gen.2 Type C - TBT3 up to 60 W (PD v2.0-1.1), 5-20V, 3.0A upstr (PC) 1 x USB3.1 Gen.2 Type C - TBT3 up to 15 W (PD v2.0-1.1), 5V, 3.0A downstr 4.5W power output to client USB 3.2 Gen 1 (5 Gbps) total 2 x Type-A - 4,5W 1 x Type-A - 12W USB 3.2 Gen 2 (10 Gbps) total 1 x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input DisplayPort 2 (up to 2560 x 1600) HDMI 1 Kensington Lock support 1 LAN / Ethernet (RJ45) Dimensions (W x D x H) 2 39 x 80 x 26 mm	DC-in	1 (19V)
USB 3.1 Gen2 total 1x USB3.1 Gen.2 Type A - 5V, 2,4A, 4,5W charging port 2x USB3.1 Gen.2 Type C - 5V, 1,5A, 15W charging port 1x USB3.1 Gen.2 Type C - TBT3 up to 60 W (PD v2.0-1.1), 5-20V, 3.0A upstr (PC) 1x USB3.1 Gen.2 Type C - TBT3 up to 15 W (PD v2.0-1.1), 5V, 3.0A downstr 4.5W power output to client USB 3.2 Gen 1 (5 Gbps) total 2x Type-A - 4,5W 1x Type-A - 12W USB 3.2 Gen 2 (10 Gbps) total 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input DisplayPort 2 (up to 2560 x 1600) HDMI 1 Kensington Lock support 1 LAN / Ethernet (RJ45) 1 Dimensions (W x D x H) 239 x 80 x 26 mm	Power on switch	1
2x USB3.1 Gen.2 Type A - 5V, 09A, 4,5W charging ports 2x USB3.1 Gen.2 Type C - 5V, 1,5A, 15W charging port 1x USB3.1 Gen.2 Type C - TBT3 up to 60 W (PD v2.0-1.1), 5-20V, 3.0A upstr (PC) 1x USB3.1 Gen.2 Type C - TBT3 up to 15 W (PD v2.0-1.1), 5V, 3.0A downstr 4.5W power output to client USB 3.2 Gen 1 (5 Gbps) total 2x Type-A - 4,5W 1x Type-A - 12W USB 3.2 Gen 2 (10 Gbps) total 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input DisplayPort 2 (up to 2560 x 1600) HDMI 1 Kensington Lock support 1 LAN / Ethernet (RJ45) 1 Dimensions (W x D x H) 239 x 80 x 26 mm	Audio	Combo jack for headset usage
1x Type-A - 12W USB 3.2 Gen 2 (10 Gbps) total 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input DisplayPort 2 (up to 2560 x 1600) HDMI 1 Kensington Lock support 1 LAN / Ethernet (RJ45) 1 Dimensions (W x D x H) 239 x 80 x 26 mm	USB 3.1 Gen2 total	2x USB3.1 Gen.2 Type A - 5V, 09A, 4,5W charging ports 2x USB3.1 Gen.2 Type C - 5V, 1,5A, 15W charging port 1x USB3.1 Gen.2 Type C - TBT3 up to 60 W (PD v2.0-1.1), 5-20V, 3.0A upstream (PC) 1x USB3.1 Gen.2 Type C - TBT3 up to 15 W (PD v2.0-1.1), 5V, 3.0A downstream
1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input DisplayPort 2 (up to 2560 x 1600) HDMI 1 Kensington Lock support 1 LAN / Ethernet (RJ45) 1 Dimensions (W x D x H) 239 x 80 x 26 mm	USB 3.2 Gen 1 (5 Gbps) total	71 7
HDMI 1 Kensington Lock support 1 LAN / Ethernet (RJ45) 1 Dimensions (W x D x H) 239 x 80 x 26 mm	USB 3.2 Gen 2 (10 Gbps) total	/1
Kensington Lock support 1 LAN / Ethernet (RJ45) 1 Dimensions (W x D x H) 239 x 80 x 26 mm	DisplayPort	2 (up to 2560 x 1600)
LAN / Ethernet (RJ45) 1 Dimensions (W x D x H) 239 x 80 x 26 mm	HDMI	1
Dimensions (W x D x H) 239 x 80 x 26 mm	Kensington Lock support	1
	LAN / Ethernet (RJ45)	1
Order code S26391-F3357-L100	Dimensions (W x D x H)	239 x 80 x 26 mm
	Order code	S26391-F3357-L100



Thunderbolt™ 3 Port-Replicator for CELSIUS Workstations Technical details

recimited details	
DC-in	1 19V/65W
Audio: line-in / microphone	1
Audio: line-out / headphone	1
USB 2.0 total	2
USB 3.1 Gen1 (USB 3.0) total	2
USB Type-C (to PC/Tablet)	1 Data connection; NO power supply to mobile Workstation
DisplayPort	2x DP 1.2 (1x through from Portrep TypeC, 1x via Portrep internal DP-Splitter; No DP++ support), resolution up to 3840 x 2160
VGA	1x (via Portrep internal DP-splitter) resolution up to 1920 x 1200, 16M colors, 60Hz
DVI	1x (via Portrep internal DP-splitter) resolution up to 1920 x 1200, 16M colors, 60Hz
Dimensions (W x D x H)	370 x 46 x 22.7 mm
Weight	0.260 kg
Order code	S26391-F2249-L100(incl. powersupply for portreplikator only/separate AC-adapter for mobile Workstation mandatory)



USB Port Replicator PR8.1

Technical details

DC-in	5V, 4A
Audio: line-in / microphone	1
Audio: line-out / headphone	1
USB 3.1 Gen1 (USB 3.0) total	3 (one BC1.2 charging)
USB charger	1
USB upstream	1
DisplayPort	1
VGA	supported with adapter S26391-F6055-L260 (not included)
DVI	1 (DVI-I, Single-Link)
HDMI	1
Kensington Lock support	no
LED	Power (blue)
Dimensions (W x D x H)	189 x 75 x 26 mm
Weight	195 gr
Order code	S26391-F6007-L410



USB Port Replicator PR09

Technical details

DC-in	20V
Power on switch	1 default: ON (PR09 from Rev.:02)
Audio	1 SPDIF (2.0)
USB Type-C cable	1 (5A Gen2) (package content)
USB downstream	7 (4xUSB-A & 3xUSB-C)
USB upstream	via USB Type-C cable (1m)
DisplayPort	2 (DP1.2a as Dualmode DP++)
USB power delivery	ver 3.0
USB Type-A 3.1 Gen1 (DFP)	4
USB Type-C (UFP)	1 w/ USB PD (60W)
USB Type-C 3.1 Gen2 (DFP)	3 thereof 1x BC1.2 w/ 10.5W
Kensington Lock support	yes
LED	On/Off switch (blue), USB Power Delivery (amber), USB connection (green), LAN traffic, rear side (green/yellow)
Compatibility	With all DisplayLink based USB Port Replicators
Dimensions (W x D x H)	200 x 97.6 x 29 mm
Weight	340 g (device only w/o AC-Adapter)
Order code	S26391-F6007-L500



USB 3.0 Hub 4 Ports

Teenmeen details	
USB 3.1 Gen1 (USB 3.0) total	4
USB downstream	4
USB upstream	1
LED	4
Dimensions (W x D x H)	100 x 62,5 x 23 mm
Weight	70 gr



More information

Fujitsu products, solutions & services

In addition to FUJITSU Accessory, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Accessory , please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/emeia/products/computing/peripheral/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2020-06-05 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH