

Technical Specifications

APC Easy UPS SRV RM 10000VA 230V ,with RailKit, External Battery Pack | SRV10KRIRK | Downloaded on 05/30/2019 (EST)



APC Easy UPS SRV RM 10000VA 230V ,with RailKit, External Battery Pack

SRV10KRIRK

Call for More Information +45 88 30 20 10

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: CD with software, Rack Mounting support rails, User Manual

Output

Output power capacity	10.0kWatts / 10.0kVA
Max Configurable Power (Watts)	10.0kWatts / 10.0kVA
Nominal Output Voltage	230V
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Waveform type	Sine wave

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard Wire 3-wire
Other Input Voltages	220, 240

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

Physical

Maximum Height	173MM, 17.3CM
Maximum Width	438MM, 43.8CM
Maximum Depth	710MM, 71.0CM

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Physical

Net Weight	69.0KG
------------	--------

Environmental

Operating Temperature	0 - 40 °C
-----------------------	-----------

Operating Relative Humidity	0 - 95 %
-----------------------------	----------

Operating Elevation	0-3000meters
---------------------	--------------

Storage Relative Humidity	0 - 95 %
---------------------------	----------

Storage Elevation	0-14763.6meters
-------------------	-----------------

Sustainable Offer Status

RoHS	Compliant
------	-----------

REACH	REACH: Contains SVHCs
-------	-----------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.