## QuickSpecs

Overview



#### **Models**

HP USB Keyboard

QY776AA

#### Introduction

The new HP USB Keyboard features an impressively durable design built for ease of use and everyday business computing.

## **Key Benefits**

- Adjustable to 0°, 6° or 12° slopes with tilt legs to suit a variety of typing preferences.
- Built for durability and heavy usage, including a lifecycle rating up to 20 million keystrokes.
- Minimize damage from minor spills with the integrated spill-drain feature.
- Expect a fast set-up with quick and easy deployment for your IT atmosphere.

## Compatibility

The HP USB Keyboard is compatible with the HP Compaq 4300 Pro AIO.

NOTE: Not all models are available in all regions.

## Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.



# QuickSpecs

**Technical Specifications** 

**HP USB Keyboard** 

Physical	Keys	104, 105, 106, 107, 109 layout (depending upon country)
characteristics	, ,	18.12 x 6.47 x 0.96 in (46.03 x 16.43 x 2.44 cm)
-	Weight	2 lb (0.9 kg) minimum
Electrical	Operating voltage	+ 5VDC ± 5%
	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI – RFI Miaraaaft® DC 00	Conforms to FCC rules for a Class B computing device
	Microsoft® PC 99 – 2001	Functionally compliant
Mechanical	Keycaps	Low-profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
	Acoustics	43-dBA maximum sound pressure level
Environmental	Operating temperature	9 50° to 122° F (10° to 50° C)
	Non-operating temperature	-22° to 140° F (-30° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidit	<b>y</b> 20% to 80% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	30 in (76.2 cm) on concrete, 16-drop sequence
Operating system support	Windows 2000, Windows	64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, XP Professional or Windows XP Home 32*. No driver is required for this provided by the operating system.
A	* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit http://www.windowsvista.com/upgradeadvisor. For Windows Vista system requirements, visit http://www.windowsvista.com/systemrequirements. UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, KC	
Approvals		
Ergonomic compliance Kit contents	e ANSI HFS 100, ISO 924 Keyboard, installation gu	ide, warranty card, safety and comfort guide



#### **Technical Specifications**

© Copyright 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are US registered trademarks of Microsoft Corporation.

