

Manhattan USB-C Dock/Hub with Card Reader and MST, Ports (x9):

: Audio 3.5mm - DisplayPort - Ethernet - HDMI - USB-A (x3) - USB-C and VGA - With Power Delivery (100W) to USB-C Port (Note add USB-C wall charger and USB-C cable needed),All Ports can be used at the same time - Dockingstation - USB-C 3.2 - VGA - HDMI - DP - GigE

Gruppe	USB-Hubs
Hersteller	Manhattan
Hersteller Art. Nr.	153478
EAN/UPC	0766623153478



Beschreibung

Manhattan USB-C Dock/Hub with Card Reader and MST, Ports (x9): Audio 3.5mm, DisplayPort, Ethernet, HDMI, USB-A (x3), USB-C and VGA, With Power Delivery (100W) to USB-C Port (Note add USB-C wall charger and USB-C cable needed),All Ports can be used at the same time - Dockingstation - USB-C 3.2 - VGA, HDMI, DP - GigE

Hauptmerkmale

Produktbeschreibung	Manhattan USB-C Dock/Hub with Card Reader and MST, Ports (x9): Audio 3.5mm, DisplayPort, Ethernet, HDMI, USB-A (x3), USB-C and VGA, With Power Delivery (100W) to USB-C Port (Note add USB-C wall charger and USB-C cable needed),All Ports can be used at the same time - Dockingstation - USB-C 3.2 - VGA, HDMI, DP - GigE
Produkttyp	Dockingstation
Docking-Schnittstelle	USB-C 3.2
Videoschnittstellen	VGA, HDMI, DP
Abmessungen (Breite x Tiefe x Höhe)	26 cm x 8.7 cm x 2.5 cm
Gewicht	340 g
Farbe	Grau
Netzwerk	Gigabit Ethernet

Ausführliche Details

Allgemein

Produkttyp	Dockingstation
Breite	26 cm
Tiefe	8.7 cm
Höhe	2.5 cm
Gewicht	340 g

Farbe	Grau
	Video
Details zur max. Auflösung	3840 x 2160
	Netzwerk
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
	Erweiterung/Konnektivität
Schnittstellen	1 x Audio / Video - HDMI - 19-poliger HDMI Typ A 2 x USB 3.2 Gen 1 - 9-poliger USB Typ A 1 x USB-C mit Stromversorgung (100 W) - 24-poliger USB-C 1 x Audio / Video - DisplayPort 1 x Video - VGA - 15-polige HD D-Sub (HD-15) 1 x USB 2.0 - 4-polig USB Typ A 1 x Netzwerk - 10Base-T/100Base-TX/1000Base-T - RJ-45 1 x Audio - Mini-Phone Stereo 3,5 mm
Kompatible Steckplätze	1 x microSD 1 x SD-Speicherkarte
	Verschiedenes
Enthaltene Kabel	1 x USB-C Kabel - integriert - 20 cm
Leistungsmerkmale	Aluminiumgehäuse, HDCP Compliant, MST (Multi-Stream Transport), Bus-betrieben, 100 W-Spannungsversorgung
Kennzeichnung	Plug and Play, FCC, RoHS
	Systemanforderungen
Erforderliches Betriebssystem	Linux, Apple MacOS X 10.7.x oder höher, Microsoft Windows 7 / 8.1 / 10
	Herstellergarantie
Service und Support	Begrenzte Garantie - 3 Jahre
	Umgebungsbedingungen
Min Betriebstemperatur	0 °C
Max. Betriebstemperatur	50 °C

Technische Daten © 1WorldSync. Technische Änderungen und Irrtümer vorbehalten.