SIG100 LITE

SIGNATURE PAD WITHOUT LCD

Sig100 LITE is a cost-effective signature pad, without LCD.

Instead of the LCD screen, the pad is composed by a special hard-wearing writing surface for precise signature capture.

Signature appears in real-time on the computer monitor, but not on the pad. It is the ideal product for applications where customers only need to provide a signature.

P/N:
ST-LTE105-2-UEVL

SUPPORTED OS
Windows® XP 32/64, W7 32/64, W8 32/64, W10 32/64
Server 2003, 2008, 2010
Linux

CERTIFICATIONS AND STATEMENT OF COMPLIANCE
TUV
CE, FCC
RoHS
EN 60950-1, EN 61000-6-1, EN 61000-6-3

PROTECTION CLASS
IP52

TECHNICAL DATA

GENERAL FEATURES	• Slim and ergonomic design • Standard stylus • Tether • 2 LED status indicators
SENSOR	• Resistive touch technology • Active signing area: 95 x 47 mm • Resolution 4036 x 4036 pixels / 2214 x1130 ppi • Linearity: +/- 1.5% in x, y and z directions • 1024 pressure levels
SIGNATURE DIGITIZATION	• External sampling rate: 500 Hz (samples per second), 4 axes (x, y, time and pressure) • Internal sampling rate: 6000 Hz (samples per second)
SECURITY	• AES encryption of data transfer between the pad and the computer • RSA signature and encryption in the pad • Unique internal serial number
SIZE AND WEIGHT	• 10 x 160 x 120 mm (0.39'' x 6.29'' x 4.72'') • 200 g (0,44 lbs)
INTERFACE	• Full-speed (12 Mbps) USB 2.0 HID (Human Interface Device) compatible with earlier versions
POWER	• Via USB cable, no external power supply
SOFTWARE	• Compatible with signoSign/2 software for creating and signing secure PDF documents • Free SDK available upon request: - Definition of signature area - Signature capture in various formats - RSA-signing functionality in the pad - Documentation available on demand • Free Tools and Twain driver available at www.evolis.com
WARRANTY	• 2 years

© 2017 Evolis. Please note that specifications and details are subject to change without notice and should therefore be confirmed by Evolis prior to any purchase. 09/2017 KB-SIG1-236-ENG-A4-A0