

Technical Specifications

APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz | AP4424A | Downloaded on 11/02/2022 (EST)

APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz

AP4424A

Call for More Information 0800 2799254



- Includes: Mounting hardware, Rack mounting brackets, Serial configuration cable

Output

Always on Outlets	18
Overload Protection	Yes
Maximum Total Current Draw	32

Input

Input frequency	50/60 Hz
Input Connections	IEC 60320, IEC 60320 IEC 60309 32 A 2P + E
Cord Length	2.4meters
Acceptable Input Voltage	207 - 253VAC
Number of Power Cords	2
Load Capacity	7400VA

Physical

Maximum Height	88MM, 8.8CM
Maximum Width	432MM, 43.2CM
Maximum Depth	236MM, 23.6CM
Rack Height	2U
Net Weight	6.94KG
Color	Black

Environmental

Operating Temperature	-5 - 45 °C
-----------------------	------------

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %

Conformance	
Approvals	EN 55022 class A, FCC part 15 class A
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
Other Environmental Compliance	China RoHS

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.