

Technical Specifications

APC Netshelter Rack Automatic Transfer Switch, 1U, 15A, 100/120V, 5-15 IN, 10 5-15R OUT, 50/60Hz | AP4450A | Downloaded on 11/02/2022 (EST)

APC Netshelter Rack Automatic Transfer Switch, 1U, 15A, 100/120V, 5-15 IN, 10 5-15R OUT, 50/60Hz

AP4450A

Call for More Information 0800 2799254



- Includes: Mounting hardware, Rack mounting brackets, Serial configuration cable

Output	
Nominal Output Voltage	120V
Overload Protection	No
Cord Length	2.4meters
Maximum Total Current Draw	15

Input	
Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P 12 A 2P + E
Cord Length	2.4meters
Acceptable Input Voltage	90 - 110VAC
Number of Power Cords	2
Load Capacity	1440VA
Maximum Input Current	15A
Maximum Line Current	15A
Regulatory Derated Input Current (North America)	15A

Physical	
Maximum Height	44MM, 4.4CM
Maximum Width	432MM, 43.2CM
Maximum Depth	236MM, 23.6CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Netshelter Rack Automatic Transfer Switch, 1U, 15A, 100/120V, 5-15 IN, 10 5-15R OUT, 50/60Hz | AP4450A | Downloaded on 11/02/2022 (EST)

Physical	
Rack Height	1U
Net Weight	4.4KG
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	FCC part 15 class A, ICES-003, PSE, TÜV-C, TÜV-NURTL, VCCI class A
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
Other Environmental Compliance	China RoHS

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.