



1D & 2D



DPM











1.8M drop

RS232













LED

aimer

Warranty 5 Years



Features

High-Performance DPM Scanning

The NVH220 Lophius stands out with its exceptional proficiency in decoding DPM barcodes, including those made by laser part marking and dotting techniques. With dual-core parallel processing and improved computing power, the NVH220 significantly enhances image capture, recognition, and scanning speed, ensuring accurate and efficient decoding.

Highly Durable In Tough Environments

Designed with durability in mind, the NVH220 Lophius features a robust design that can withstand the toughest conditions. With its high-protection construction and IP64-sealed housing, this scanner ensures reliable performance, even in the face of dust, water, and repeated falls from heights of up to 1.8 meters.

Intelligent Learning

With the intelligent learning ability, the NVH220 Lophius enables automatic parameter adjustments based on previous scanning scenarios, ensuring optimal performance and adaptability. Leveraging three illumination colors and intelligent angle adjustments, the NVH220 Lophius automatically explores the options to

find the optimal combination for scanning. Once identified, this scanner memorizes the last setting, ensuring efficiency in future code scans.

Advanced Illumination and AI Functionality

The NVH220 Lophius comes equipped with diverse lighting options, encompassing direct white and red illumination, along with diffuse blue ring lights. These advanced illumination capabilities empower the NVH220 Lophius to effortlessly scan even the most demanding barcodes across a diverse spectrum of materials (reflective surface), shapes (curved surfaces), backgrounds (low to high contrast), and barcode colors. With advanced AI capabilities, the NVH220 Lophius excels in barcode positioning and reconstruction, further enhancing its ability to tackle challenging barcodes.

Configure To Your Needs

With free configuration software Nset, the NVH220 Lophius can be easily configured to suit the needs of any application. Nset is specifically tailored for DPM and high-density scanners, providing users with enhanced flexibility and control over their devices.



Suggested industries













Manufacturing

Transportation

NVH220 Lophius Corded Technical specifications

_		-			
Пa	ta.	Ca	n	tu	ra
$\mathbf{\nu}$ a	LCL	$\mathbf{v}^{\mathbf{u}}$	ν.	u	

1D EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code128, Code93, Code11, COOP25, GS1-128 (UCC/EAN-128), ITF-6, ITF-14, AIM128, ISBT128, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2

of 5, MSI Plessey, Code 39, Plessey, Deutsche 14, Deutsche 12

2D QR Code, PDF417, Micro QR, Data Matrix, Aztec

Image Sensor 1280 × 960 CMOS

Aiming LED 532nm

Illumination Direct: white & red light LED; Diffuse: ring of blue LED

Horizontal 41°, Vertical 31°

Resolution ≥3mil

Depth of Field EAN 13 (13mil) 25mm-160mm

Depth of Field Code 39 (20mil) 35mm-210mm

Depth of Field DataMatrix (10mil) 0mm-125mm

Depth of Field QR (20mil) 20mm-180mm

Scan Angle Roll: 360°, Pitch: ±50°, Skew: ±50°

Motion Tolerance 2m/s

Minimal Print Contrast 20%

Physical

Field of View

Current @ 5VDC Operating typical: 450mA; max: 475mA

Dimensions (mm) 67(W)×86(D)×170(H) mm

Input Voltage 5VDC±5%

Interfaces USB, RS232

Notifications Beep, LED indicator, Vibrator

Power Consumption 2250mW (typical)

Weight 245g

Environmental

Storage Temperature -40°C to 70°C(-40°F to 158°F)

Operating Temperature/Storage Temperature -20°C to 50°C(-4°F to 122°F); -40°C to 70°C(-40°F to 158°F)

Humidity 5% to 95% (non-condensing)

Electro Static Discharge (ESD) ±16 KV (air discharge); ±8 KV (direct discharge)

Drop 1.8m

IP Rating IP64

Accessories

Standard USB, RS-232

Certifications

Hardware FCC, CE, ROHS, IEC63471

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

