



34" IPS ultra-wide flat screen with PiP, PBP and height adjustable stand

With a 21:9 UWQHD resolution, the ProLite XUB3493WQSU provides an extended desktop space ideal for working with multiple applications side by side. The IPS panel ensures accurate colour reproduction and wide viewing angles, suitable for both detailed work and media consumption. Equipped with Picture-in-Picture (PiP) and Picture-by-Picture (PbP) functionalities, the monitor allows you to display content from two different sources simultaneously. This is especially useful for professionals who need to monitor multiple systems or compare data across devices without the need for a second screen.

The 150 mm height-adjustable stand helps you maintain an ergonomic posture, while flicker-free technology and a blue light reducer contribute to reduced eye fatigue. The XUB3493WQSU offers a practical and flexible solution for users who value efficiency, clarity, and comfort.



IPS Technology

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



ULTRA WIDE - UWQHD

UWQHD (Ultra Wide QHD) resolution offers an ultra wide (21:9) viewable area.

01 DISPLAY CHARACTERISTICS

Diagonal	34", 86.7cm
Panel	IPS panel technology LED
Native resolution	3440 x 1440 @120Hz (4.9 megapixel UWQHD)
Aspect ratio	21:9
Panel brightness	400 cd/m ²
Static contrast	1000:1
Advanced contrast	80M:1
Response time (MPRT)	1ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn 8bit (sRGB: 100%, NTSC: 74%)
Horizontal Sync	30 - 185kHz
Viewable area W x H	799.8 x 334.8mm, 31.5 x 13.2"
Pixel pitch	0.233mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0) DisplayPort x1 (v.1.2)
USB HUB	x4 ((2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W)))
HDCP	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	HDMI & Display Port: 3440 x 1440 @48-120Hz
HDR	yes
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu, Adjust/Volume/Mute, Adjust/Shortcut, Input/Exit
User controls	picture (video mode adjust, brightness, contrast, black tuner, sharpness, OD, ACR, Eco, X-res Technology), colour adjust (colour temperature, user colour, i-Style colour, blue light reducer, gamma), PiP/PbP (PiP/PbP mode, sub win input, PiP size, PiP position, swap, audio input), input select (input source), audio (volume, mute), language, OSD (OSD H. position, OSD V. position, OSD background, OSD time out), setup menu (reset, USB charge, DDC/CI Control, HDMI range, HDR, Adaptive Sync, motion blur red., opening logo, power LED, information
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC/CI, Mac OSX

04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	150mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI, DP
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	44W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	CE, TÜV-GS, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
REACH SVHC	above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	817 x 428.5 (572.5) x 245.5mm
Box dimensions W x H x D	900 x 188 x 456mm
Weight (without box)	9.6kg
Weight (with box)	11.9kg
EAN code	4948570125609

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED