



Transcend's SATA III 6Gb/s SSD370S boasts incredibly fast transfer speeds, MLC NAND flash memory, a compact and lightweight design, and shock and vibration resistance. With this solid state drive, you will enjoy a seamless, lag-free computing experience.



MLC NAND flash inside

Transcend's SSD370S is manufactured with reliable, top-tier MLC NAND flash memory to ensure superior stability and endurance, making it well-suited to high-end applications.



Performance boost for everyday computing

Taking full advantage of the SATA III 6Gb/s interface, DDR3 DRAM cache and a powerful controller, Transcend's SSD370S delivers blazing-fast read and write speeds of up to 560MB/s and 460MB/s.



Guaranteed endurance and reliability

Transcend's SSD370S offers great Terabytes Written (TBW) values (up to 408 TB) indicating the total amount of data you can write into the drive over its lifetime. It also features Error Correcting Code (ECC), Garbage Collection, Wear-leveling, and DevSleep.





2.5" Solid State Drive SATA III 6Gb/s SSD370S

Features

- · Up to 560 MB/s read; 460 MB/s write
- MLC NAND flash memory and DDR3 DRAM cache
- Engineered with ECC (Error Correcting Code) to ensure data integrity
- Supports DevSleep ultra low power state, S.M.A.R.T., TRIM, and NCQ commands
- Download the SSD Scope software from Transcend's official website



SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

Specification

Specification		
Appearance		
Dimensions (Max.)	100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")	
Weight (Max.)	63 g (2.22 oz)	
Storage		
Flash Type	MLC NAND flash	
Capacity	32 GB / 64 GB / 128 GB / 256 GB / 512 GB / 1 TB	
Operating Environmen	it	
Operating Temperature	0°C (32°F) ~ 70°C (158°F)	
Operating Voltage	5V±5%	
Performance		
Sequential Read/Write (ATTO, max.)	Read: 560 MB/s Write: 460 MB/s	
Sequential Read/Write (CrystalDiskMark, max.)	Read: 520 MB/s Write: 460 MB/s	
4K Random Read/Write (lOmeter, max.)	Read: 75,000 IOPS Write: 75,000 IOPS	
Mean Time Between Failures (MTBF)	1,000,000 hour(s)	
Terabytes Written (Max.)	408 TB	
Drive Writes Per Day (DWPD)	0.19 (3 yrs)	
Note	Speed may vary due to host hardware, software, usage, and storage capacity.	
Warranty		
Certificate	CE/FCC/BSMI	
Warranty	Three-year Limited Warranty	

Ordering Information

32GB	TS32GSSD370S		
64GB	TS64GSSD370S		
128GB	TS128GSSD370S		
256GB	TS256GSSD370S		
512GB	TS512GSSD370S		
1TB	TS1TSSD370S		

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



2.5″ SSD	Transcend*	Transcend*	Transcend*		
Comparison					
	55D2305 Seef State State	SSD2205 Sections the	SSD3705 Selet tree Drive		
	SATA III 6Gb/s	SATA III 6Gb/s	SATA III 6Gb/s		
	SSD230S	SSD220S	SSD370S		
Appearance					
Dimensions (Max.)	100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")				
Weight (Max.)	53 g (1.87 oz)	45 g (1.59 oz)	63 g (2.22 oz)		
C+					
Storage					
Flash Type	3D NAND flash	3D NAND flash	MLC NAND flash		
Capacity 	128GB ~ 2TB	120GB ~ 960GB	32GB ~ 1TB		
Operating Environment					
Operating Temperature	0°C (32°F) ~ 70°C (158°F)	0°C (32°F) ~ 60°C (140°F)	0°C (32°F) ~ 70°C (158°F)		
Derfermense					
Performance					
Sequential Read/Write (ATTO, max.)		-	560 MB/s 460 MB/s		
Sequential Read/Write	560 MB/s	550 MB/s	520 MB/s		
(CrystalDiskMark, max.)	520 MB/s	500 MB/s	460 MB/s		
4K Random Read/Write (IOmeter, max.)	85,000 IOPS 89,000 IOPS	65,000 IOPS 75,000 IOPS	75,000 IOPS 75,000 IOPS		
Mean Time Between Failures	89,000 IOF 3	75,000 10 5	73,000 IOF3		
(MTBF)	1,000,000 hour(s)	1,000,000 hour(s)	1,000,000 hour(s)		
Terabytes Written (Max.)	1,120 TB	320 TB	408 TB		
Drive Writes Per Day (DWPD)	0.3 (5 yrs)	0.3 (3 yrs)	0.19 (3 yrs)		
Marranty					
Warranty Warranty	Five-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty		
		Thee-year Linned Warranty			
Technology					
TRIM & NCQ Command	\checkmark	~	\checkmark		
S.M.A.R.T.	· · · · · · · · · · · · · · · · · · ·	` 	 		
DDR3 DRAM Cache	 ✓	-	\checkmark		
Advanced Garbage Collection	\checkmark	~	\checkmark		
DevSleep Mode	\checkmark	\checkmark	\checkmark		
RAID Engine	\checkmark	\checkmark	-		
LDPC Coding	\checkmark	~	-		

 $\ast \mbox{Speed may vary due to host hardware, software, usage, and storage capacity.$